



TECHNICAL DATASHEET

JETPRO 80 / REF.30555

ATOMIZER



JETPRO 80 is a machine for applying thin films of filler.

It uses a valveless pump, is easy to maintain, with a round stainless steel tank for easy cleaning, a Ø35 mm drain valve. It is equipped with large diameter, flat profile, inflatable tyres for better stability.

The machine is equipped with a ball nose pump with integrated filter. Starting is wireless when the gun is opened.

The quick-release hoses make it easier to use on site.

APPLICATIONS

All types of ready-to-use film plasters: smoothing coating, raking coating, casing coating, bituminous coating ...

Can also make droplet type applications with an optional kit and a compressor.

Maximum working pressure	100 bar
Maximum product flow-rate	6 L/min
Electric motor	2,2 kW
Power	230 V / 50 & 60 Hz
Type of pump	volumetric screw
Pump	JET 1
Tank capacity	40 L
Maximum tip size (new)	0,045"
Dimensions (L x w x h)	113 x 61 x 78 cm
Weight	80 kg
Noise level	91 Lwa

DELIVERED WITH

- a Ø16 x 10 m hose
- a spray-gun with tip holder
- a Standard 535 tip
- a toolbox containing:
 - two spanners 17 and 22
 - a multigrip plier
 - three Allen keys Ø2, 5 and 8
 - two cleaning balls and a cleaning brush
 - 1 L of storage liquid



EUROMAIR