



TECHNICAL DATASHEET

COMPACT-PRO 35/ REF.30733

SPRAYING MACHINE



Spraying machine for mortars and exterior coatings. Equipped with a stainless steel tank, a digital control panel and a twin-cylinder compressor.

APPLICATIONS

Traditional mortars with admixtures, hydraulic coatings, monolayers, lime-based coatings, high-load technical and special coatings, repointing coatings...

With optional lance and pump:

Glues and E.W.I. coatings, thick plastic coatings, light hydraulic coatings...

Product pressure	0 to 20 bar
Product flow-rate	0 to 30 kg/min
Machine motor power	2,2 kW
Comp. absorbed air flow-rate	366 L/min
Compressor power	2,2 kW
Maximum air pressure	10 bar
Power supply	230 V - 16 A - 50 Hz
Tank capacity	100 L
Maximum grain size	6 mm
Pump	MAP 6
Integrated vibrator	yes
Dimensions (L x w x h)	130 x 70 x 75 cm
Weight	143 kg
Noise level	96 Lwa

DELIVERED WITH

- a Ø32 mm x 10 m air/product hose
- a pressure controller with adapter
- a carry-case containing:
 - an ABS mortar spray lance
 - eight spraying nozzles (Ø8, 10, 12, 14, 16, 18, 20 & 22 mm)
 - three grouting nozzles (Ø10, 12 & 14 mm)
 - two cleaning balls and a tube brush
 - a cleaning brush
 - an unplugging brush
 - a 7 mm Allen key

