

TECHNICAL DATASHEET

Petrol high pressure washer EUROPROLAV 15-250 TH.2 | ref.30858



EUROPROLAV 15-250 TH.2 is a compact, robust washer.

It is suitable for intensive use on all types of jobs.

It is equipped with locations to reel water inlet and lance hoses, a thermostatic valve, a low-oil safety system, a spray-gun with rotating coupling, a double lance and a lance with rotating nozzle.

Equipped with large diameter wheels and a reinforced chassis, it is easy to handle. Designed for easy maintenance.

Variable pressure	0 to 250 bar
Flow-rate	15 L/min
Nozzle	15°- 40
Motor power	VANGUARD 14 HP
Fuel used	unleaded 98
Tank capacity	6,1 L
Consumption	3,5 L/h
Lubrication	splashing
Pump	brass head, 3 ceramic pistons
Detergent suction system	no
Pump rotation	3600 RPM
Max. water temperature accepted	70°C
Lance	double with KW coupling
Hose	20 m - 315 bar
Dimensions (L x w x h)	66 x 62 x 91 cm
Weight	77 kg

Delivered with

- a 20 m high pressure hose
- a 10 m water supply hose
- a 300 mm double lance
- a 600 mm double lance
- a rotating nozzle
- a 5 L jerrycan